Lecture 19: Memory Allocation Implementation

CSE 29: Systems Programming and Software Tools

Aaron Schulman (Shalev)




Logistics



- Beginning a new phase of the class today:
 - First half of the class was focused on low-level programming in C
 - Second half of the class is focused on how a computer system works ("systems")
 - » How does memory allocation work?
 - » How does information get stored on a disk?
 - » Intro to Networking and OS: How do you build a webserver?










Malloc Implementation: Heap structure



```
int* p1 = malloc(4); // 0x00
int* p2 = malloc(8); // 0x08
int* p3 = malloc(1); // 0x10
```

Alignment Requirement for 64-bit machine:


8 bytes (every heap allocation should be aligned to 8 bytes)





Requirements:


- 1. Only use information in the heap to manage the heap
- 2. Can not modify previously allocated blocks



We also need to store metadata also in the heap about each allocation

Headers: How to store metadata on the hea






Add 8 byte headers before each allocation on the heap

```
int* p1 = malloc(4); // 0x00
int* p2 = malloc(8); // 0x08
int* p3 = malloc(1); // 0x10
```







Add 8 byte headers before each allocation on the heap

```
int* p1 = malloc(4); // 0x00
int* p2 = malloc(8); // 0x08
int* p3 = malloc(1); // 0x10
```

Header implementation



- Header contains a length and a flag bit representing free/allocated
 - Even number: representing a *free block*
 - Odd number: representing a malloc'd, allocated, busy block
- □ In both cases, the number with LSB set to 0 is the block size in bytes
- $_{\square}$ header = 33 \rightarrow allocated block of 32 bytes (24 byte payload)
- □ header = 108 → free block of 108 bytes (100 byte payload)
- "size of block" = full size including header
- Always make block sizes divisible by 8 (or 8-byte aligned)