

```

1 #include <stdio.h>
2
3 int main() {
4     char hello[] = "Hello!";
5     char hello2[] = { 72, 101, 108, 108, 111, 33, 0 };
6                     H   e   l   l   o   !   0
7     puts(hello);
8     puts(hello2);
9 }

```

```

$ gcc hello.c -o hello
$ ./hello
Hello!
Hello!

```


ASCII - most common
byte $\leftrightarrow$ char mapping

creating an array of characters

```


char s[] = "....";
char s2[] = { ..... };



```



(computers store things w/metal and electricity, not memory models!)

What happens when you press a key?






"flip flop" gate.
 Send a signal 0 or 1
 on input and flip flop
 "sticks" to that side
 (requires power)

SRAM
 - cheap (silicon)
 - small
 - fast (100M times/sec)
 - accurate


(How) Can we do better than 100 gates per character / per key? By "better" I mean fewer flip-flops per character

current picture:




100 little boxes


each little box is
this hardware:



Proposal
each key/char



(this combo means 'A')



(this combo means '%')

8 bits
= 1 byte

bits







⋮

one character is represented
by 1 byte

How many combinations of 8 bits are possible?

(How many characters represented by 1 byte?)

Combinatorics mindset: 2 choices ~~for~~ 8 times = $2^8 = 256$

	0000 0000	0
	0000 0001	1
	0000 0010	2
	0000 0011	3
	0000 0100	4
	0000 0101	5
	0000 0110	6
	0000 0111	7
	0000 1000	8
		

there are 256 rows!

1111 1111 255

What would the
01 ... for 255 be?


```

1 #include <stdio.h>
2
3 int main() {
4     char hello[] = "Hello!";
5     char hellonum[] = { 72,      101,      108,      108,      111,      33,      0 };
6     char hellobin[] = { 0b1001000, 0b1100101, 0b1101100, 0b1101100, 0b1101111, 0b100001, 0b0 };
7
8     puts(hello);
9     puts(hellonum);
10    puts(hellobin);
11
12    printf("%c %c %c\n", hello[0], hello[1], hello[2]);
13
14    printf("%d %d %d\n", hello[0], hellonum[0], hellobin[0]);
15    printf("%c %c %c\n", hello[0], hellonum[0], hellobin[0]);
16 }

```

0b _____ means writing a number (a single byte here)
 "Binary Literal" directly as bits

%c : print a value as char
 %d : print a value as decimal #

puts
 Line 12

```

$ gcc hellobin.c -o hellobin
$ ./hellobin
Hello!
Hello!
Hello!
H e l
72 72 72
H H H

```




```

1 #include <stdio.h>
2 #include <stdlib.h>
3 #include <string.h>
4
5 int main() {
6     char hello[] = "Hello class!";
7     char apple[] = "apple";
8     char hello_0[] = "Hello\0class!";
9
10    printf("%ld\n", strlen(hello));
11    printf("%ld\n", strlen(apple));
12
13    printf("%s, length: %ld\n", hello_0, strlen(hello_0));
14
15    hello[7] = 0;
16
17    printf("%s, length: %ld\n", hello, strlen(hello));
18
19    return 0;
20 }

```

these are null terminated because they are string literals (true for all string literals)



```

$ gcc strlen.c -o strlen
$ ./strlen
12
5
Hello, length 5
Hello c, length: 7

```

```

1 #include <stdio.h>
2
3 int main() {
4     char hi[] = "Hi all!";
5     char helloeveryone[] = { 'H', 'e', 'l', 'l', 'o', ' ', '!', ' ', ' ',
6                               'e', 'v', 'e', 'r', 'y', 'o', 'n', 'e', '!', '!' };
7     puts(hi);
8     puts(helloeveryone);
9 }

```

```

$ gcc adjacent.c -o adjacent
$ ./adjacent

```

Hi all!
Hello, everyone! Hi all!

